

## 55" Multi-Touch LCD Monitor (LM-5526-33 Model)

- Using NEC Display Model P551
- Optical 4 Point Multi-Touch
- Full 1080p HD Resolution (1920 x 1080)
- 3 Year Limited Warranty
- Feet Included



### Product Specifications:

<b>Size/Type</b>	55 inch Diagonal/ Active Matrix LCD Display
<b>Touch Technology</b>	Optical 4 Point Multi-Touch
<b>Brightness</b>	500 cd/m2
<b>Refresh Rate</b>	120 Hz
<b>Contents of Packaging</b>	User's Manual, AC Power cord, Wireless Remote, Batteries, 15-pin RGB Cable, CD-ROM, Setup Sheet & Driver CD
<b>Contrast Ratio</b>	3000:1
<b>Colors</b>	more than 16 million (depending on video card used)
<b>Optional</b>	TV Tuner, Built-in PC or External Speakers
<b>Dimensions</b>	Net with stand: 49.2" (W) x 29.8" (H) x 15.8" (D) / 1250 x 757 x 400 mm Net without stand: 49.2" (W) x 28.4" (H) x 5.9" (D) / 1250 x 721.1 x 150 mm
<b>Input</b>	DVI-D, HDMI, DisplayPort, Analog VGA, Analog 5 BNC, Composite RCA, Component RCA, S-Video, Composite BNC
<b>Input Signal</b>	Video: ANALOG RGB 0.7 Vp-p / 75 Ohms Separate sync: TTL Level (Positive/Negative) Composite sync: TTL Level (Positive/Negative) Composite sync on green: (0.3Vp-p negative 0.7Vp-p positive)
<b>Limited Warranty</b>	3 year including backlight
<b>Operating Altitude</b>	3000m/9842.5 ft.
<b>Operating Humidity</b>	20-80%
<b>Operating Temperature</b>	5-40 C/41-104 F
<b>Pixel Pitch</b>	0.53mm
<b>Power Consumption</b>	On: 280W / Power Savings Mode: <.5W
<b>Resolutions Supported</b>	640x480, 800x600, 1024x768, 1280x768, 1360x768, 1280x1024 1600x1200(Compressed), 1920x1080 (Recommended)
<b>Storage Altitude</b>	40,000ft / 12,192m
<b>Storage Humidity</b>	10-90%
<b>Storage Temperature</b>	-20-60 C/-4-140 F
<b>VESA Hole Configuration Spec.</b>	400 x 400 mm (4 hole)
<b>Viewing Angle</b>	Up 89 / Down 89 / Left 89 / Right 89 (typ.)
<b>Voltage Rating</b>	AC 100-120V / AC 220-240V @ 50/60 Hz
<b>Weight</b>	Net without stand: 90 lbs.
<b>Output</b>	RGB/HV, Video, Audio: Stereo Mini Jack, Optical S/PDIF Control: RS232 for multiple monitor control, Audio Amplifier: 7W x 7W
<b>Additional Features</b>	Power Management Plug and Play (DDC/CI DDC2B) PIP (Remote) Multi level Zoom, FullScan, 6 axis color CableComp TileMatrix TileComp Screen Saver Rapid Response, Video Ready (no tuner) Infrared remote control included